


PRODUCT MODEL NUMBERS

| | |
|----------|----------|
| ET1CHKXX | ET8MTEXK |
| ET1CHMXK | ET8RHMXX |
| ET1FTEXL | ET8WTEXK |
| ET1FTEXM | ET8WTEXM |
| ET1FTKXX | ET8WTKXX |
| ET1FTTXX | ET8WTMXK |
| ET1LFKXX | ET9CHKXX |
| ET1MHKXM | ET9FTKXX |
| ET1MTEXL | ET9FTTXX |
| ET1MTEXM | ET9LFKXX |
| ET1MTKXX | GR9SHKXX |
| ET1RHMXX | GR9SHKXM |
| ET1WTKXX | GT1SHTXL |
| ET8CHKXX | GT2SHKXL |
| ET8CHMXK | GT2SHKXM |
| ET8FTEXK | GT2SHMXL |
| ET8FTEXM | GT9SHKXX |
| ET8FTKXX | GT9SHKXM |
| ET8LFKXX | |

Electrical: A 115 Volt, 60 Hz., AC only 15 or 20 ampere fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.


Water: Connect the ice maker to a cold water line with water pressure between 30 and 120 psi.

OVERALL DIMENSIONS



| Model size | Depth "A" | Cab. Width "B" | Door Width "C" | Cab. Height "D" | Overall Height "E" |
|------------------------|--------------|-------------------|-------------------|--------------------|-----------------------|
| STANDARD MODELS | | | | | |
| 18 cu.ft. | 29 3/8" | 29 1/2" | 29 3/4" | 65 1/2" | 66 1/4" |
| 19 cu.ft. | 30 3/4" | 29 1/2" | 29 3/4" | 65 1/2" | 66 1/4" |
| 21 cu.ft. | 29 3/8" | 32 1/2" | 32 3/4" | 65 1/2" | 66 1/4" |
| 22 cu.ft. | 30 3/4" | 32 1/2" | 32 3/4" | 65 1/2" | 66 1/4" |
| CONTOUR MODELS | | | | | |
| 19 cu.ft. | 31 1/2" | 29 1/2" | 30 1/8" | 65 1/2" | 66 1/2" |

LOCATION REQUIREMENTS



To ensure proper ventilation for your refrigerator, allow for 1/2 in. (1.25 cm) space on each side and at the top. (At the top, when using half depth cabinet, use top of cabinet height "D" dimension. When using full depth cabinet, use overall "E" dimension.) When installing your refrigerator next to a fixed wall, leave 2 in. (5.08 cm) minimum on each side (depending on your model) to allow for the door to swing open. If your refrigerator has an ice maker, allow extra space at the back for the water line connections.

NOTE: Do not install the refrigerator near an oven, radiator, or other heat source, nor in a location where the temperature will fall below 55°F (13°C).